

Product Datasheet model ultravision 9301 105



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Product characteristics	• classic goggles with unrestricted field of vision • can be worn over prescription spectacles • lenses can be changed • high mechanical strength of the polycarbonate (B: 120 m/s) lens • innovative indirect ventilation system helps maintain a comfortable climate around the eyes • suitable for construction applications
Technical details Frame Material Features Colour	Front piece PVC ventilation system transparent light grey

Material	Headband
Features	synthetic headband
Colour	adjustable
	anthracite/lime
Manufacturer's ID	Marking
code	W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid)
	4 (large dust particles)
	9 (molten material and hot solids)
Medium-energy impact	B (120 m/s)
Conformity symbol	CE
Lens	
Material	PC
Filter	2,2 mm
Coating	supravision excellence
Colour	clear
UV protection	UV 400
	Marking
Filter	2C-1,2 (DIN EN 170)
Manufacturer's ID	W
code	
Optical class	1
Low-energy impact	B (120 m/s)
Field of use	9 (molten material and hot solids)
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Factory symbol	

Miscellaneous

Weight

130 g

Packing

90 pieces in one carton

Standards

DIN EN 166 + DIN EN 170

PPE Category

Category II